



PIPELINER II 609

ORBITAL WELD HEAD FOR MULTI-PASS GMAW/FCAW PIPE WELDING


The Magnatech Pipeliner II is designed to make pipe-to-pipe and pipe-to-fitting welds. Interchangeable guide rings mount the head on the pipe, allowing a broad workpiece size range from 168 – 1524 mm (6" – 60") and larger. The Pipeliner II improves productivity by increasing duty cycle, reducing repair rates, and producing welds of consistent quality.

- Generates high quality welds
- Simple to understand operating
- Can be operated by non-qualified/non-English speaking labour
- Extreme rugged design
- Push-pull system avoids wire feed interruption

PIPELINER II 609

TORCH OSCILLATION (WEAVE)

Width, speed, and endpoint "dwell" independently programmable. Torch "cross seam" steering electronica.



WATER-COOLED TORCH 300 A

PUSH-PULL WIRE FEED HEAD

POSITIVE WIRE DRIVE SYSTEM

Guarantees uniform rotation speed. Two heads can be mounted simultaneously on one guide ring*.

SPECIFICATIONS

*Guide rings come with a one year warranty

Application	Pipe size – 168 mm (6.625") and larger Pipe wall thickness – unlimited Flx-Track™ for welding on flat and curved surfaces	
Oscillation module (linear)		
Oscillation stroke amplitude	0 – 51 mm (2")	
Oscillation speed	0 – 2540 mm/min. (100 ipm)	
Oscillation dwell	0 – 1 second. Independently adjustable at both stroke endpoints	
Cross seam adjustment	± 25 mm (1.0")	
Oscillation module (pendular)	Allows sockets/fillet welding	
Cross seam adjustment	± 20 degrees	
Torch vertical motion module	Stroke: 66 mm (2.625") (motorized) Speed: 1520 mm/min. (60 ipm) maximum	
Tractor module	Poly-Track® propulsion (patented)	
Speed capability	0 – 762 mm/min. (30 ipm). Higher speed motors available	
Travel direction	Switch selectable (on head)	
Wire	Wire diameter:	0.8 – 1.6 mm (0.03 – 0.62")
	Wire feed speed:	0.5 – 22 m/min. (20 – 866 ipm)
	Wire spool size:	15/16 kg (25/33 lbs)
Water-cooled torch	Amperage capability: 300 amps continuous. Uses standard torch components	
Cable length	Wire feeder push-pull – 7.6 m (25') standard	
Torch adjustment capability	Torch lead/lag adjustment:	± 15 degrees (manual)
	Torch tilt adjustment:	± 10 degrees (manual)
	Angle bracket (optional):	± 45 degrees (manual)

MAGNATECH

AUTOMATIC PIPE WELDING SOLUTIONS

MAGNATECH INTERNATIONAL B.V.
De Amer 24, 8253 RC Dronten, The Netherlands
P (+31) 321 386 677 F (+31) 321 314 165
info@magnatech-international.com
www.magnatech-international.com

MAGNATECH LLC USA
6 Kripes Road, P.O. Box 260, East Granby, CT 06026-0260
P (+1) 860 653-2573 F (+1) 860 653 0486
info@magnatechllc.com
www.magnatechllc.com